DRAIN LINE JETTING EQUIPMENT

HotJet's Sewer Drain Line Jetters are engineered for the Professional Rooter, Plumber and Municipalities and will tackle the toughest blockages! Extremely effective in removing grease, soils, ice build ups, and blockages in drain lines from 2" to 12" - Easy to operate and priced right! Our Hot Jet Units are truly versatile workhorses - and they can be utilized as a dual purpose machine. First - as a powerful drain jetter and Second as a high pressure cleaning unit to clean up properties. The unit includes our

Exclusive Engineering Features and the Best Warranty in the Industry!

Trailer Colors

Red
Black
Blue
Safety Yellow

Single Engine / Gas

CLEANS 2" TO 12" LINES
TANDEM AXLE

Part Number	Description	Engine	Output*	Other Specifications
SKS23TA7350CWM	Tandem Axle w/200' x 3/8" Manual Reel	23HP Vanguard by Toyota	7GPM @ 3,500 PSI	 Drive Triple V-Belt Trailer Size 4' x 10' Deck Single Axle, Enamel Paint Axle Rating 1 x 3,500 LB. Ladder rack
SKS35TA1030CWM	Tandem Axle w/200' x 3/8" Manual Reel	35HP Vanguard by Toyota	10GPM @ 3,000 PSI	
SKS23TA7350CWE	Tandem Axle w/300' x 3/8" Electric Reel	23HP Vanguard by Toyota	7GPM @ 3,500 PSI	
SKS35TA1038CWE	Tandem Axle w/300' x 3/8" Electric Reel	35HP Vanguard by Toyota	10GPM @ 3,850 PSI	
SKS25TA9038CWCAL**	Tandem Axle w/300' x 3/8" Electric Reel	25HP Vanguard by Toyota	9GPM @ 3,850 PSI	
SKS35TA1230CWE	Tandem Axle w/300' x 3/8" Electric Reel	35HP Vanguard by Toyota	12GPM @ 3,000 PSI	
SKS27TA1520CWE	Tandem Axle w/300' x 3/8" Electric Reel	27HP Kohler/Cat Pump	15GPM @ 2,000 PSI	

Over 30 Years of Building Quality Equipment!

**CALIFORNIA AIR COMPLIANT

Exclusive Engineering Features

□ Dual Filter Intake System

We pre-plumb the pump intake so the draw water from the tank is dual filtered - one 80 mesh filter and the other a 50 mesh filter to protect the pump. This has proven to dramatically increase the pump life and reduce down time.

□ Pump

The pump systems we use are manufactured by General Pumps. The Emperor Series General Pump are proven with literally thousands in service worldwide. They are easy and inexpensive for service and we back them with a 10 year warranty.

□ Pump Saver System

We engineer all sewer jetter trailers with our "pump saver system" - that when the hose flow is released, the bypass water re-circulates back to the water tank. This keeps the head of the pump cool extending its life substantially.

☐ TBDS™ (Total Belt Driven System)

All components are belt driven. The pump is Triple-V-Belt Driven. Belt driven reduces vibration and allows the pump to run at 1/2 RPM. This extends operational life, especially vs. gear driven power plants.

□ Chemical Application

The equipment operator can control the concentration levels at the machine and controls the chemical concentration depending on the job needs.

□ Dual Antifreeze Systems

- (1) Our sewer jetter trailer units come with our quick antifreeze system where you close one valve and open the antifreeze ball valve then run the machine for 30 seconds and the entire system is antifreezed. Start the machine then recapture the antifreeze in the antifreeze tank and re-attach the jetter nozzle and you are ready to jet!
- (2) System Blow Out Attach an air hose to head of pump and open all valves.
- (3) Total System Recycle In cold weather you can also leave the equipment running and it will recycle the water back to tank.

^{*}Output +/- 5% PSI and GPM vary as per elevation, engine RPM and nozzle size.

Over 30 Years of Building Quality Equipment!

- **ROOTER COMPANIES**
- **PLUMBERS**
- MUNICIPALITIES







DWERFUL • BUILT TO LAST • BEST W

GENERAL SPECIFICATIONS

- · 330 Gallon Water Capacity
- Molded HDP Water Tank(s)
- · Adjustable Pressure Relief/Control Valve(s)
- Rear LED Lighting
- · 2" Fast Fill Pipe with 100' Fill Hose
- Full Variable Pressure and Rear Throttle Control
- 2 PSI Gauges Front and Rear

PUMP

- General Premium Emperor Series TSF2021 Pump - max output dependent upon choice of power unit
- Triple V-Belt Driven for Smooth Operation
- · Dual Safety Adjustable Blow Off Valves
- **Dual Hose Pulsation Controls**
- · Full Ten (10) Year Warranty

MOTOR DESCRIPTION

- · Engine Vanguard
- · Battery & Battery Box
- 14 Gallon Gas Fuel Tank
- Ultra Quiet Muffler
- Three (3) Year Commercial Warranty

EXCLUSIVE FEATURES

- Dual Antifreeze system
- Twin Filter System
- Pump Saver System
- Soap Injection System
- TBDS (Total Belt Driven System)
- Full Recycle System

TRAILER DESCRIPTION

- Full Premium Epoxy Paint
- · Rugged, Specially Engineered Trailer to Haul the Equipment and Water Load
- Leaf Spring Axles Cushion and Distribute the Weight for Easy
- 4'x12' Tandem Axle (2 x 3,500 lb)
- · Dual Axle Brake DOT Legal in all 50 States
- Full LED Lighting

SEWER HOSE & REEL

- · Sewer Hose 300' HD Poly Braided Construction - 12.000 PSI Burst -Cut Resistant
- Variable Speed Control Reel
- Heavy Duty 12 Volt Powered
- 120° Guide Arm with Thumb Control On/Off

OVERALL DIMENSIONS

- 16' 6" incl. hitch Overall Length
- Deck Length 12'
- Height 8' with safety light
- Overall Deck Width
- Weight (Dry) 2,300 lbs Weight (Full Load) 5,200 lbs

UPGRADES AVAILABLE

- Upgraded hose reel(s) with variable speed and guide arm available with thumb control
- · Solid State Wireless Remote Control
- HD Lockable Side Tool Boxes
- · Customized Signage
- Warthog Nozzle(s)
- · 5'x12' Custom Powder Coated Trailer
- · 2nd Power Wash Reel. Hose and Spray Gun

DISTRIBUTED BY:







