

Over 30 Years of Building Quality Equipment!

CLEANS UP TO 24" LINES



DRAIN LINE JETTING EQUIPMENT

HotJet's Xtreme Flow Sewer Drain Line Jetters are engineered for the **Professional Rooter, Plumber and Municipalities** and will tackle the toughest blockages! Easy to operate and priced right! Will handle small lateral lines with the jumper hose assembly as well as larger lines up to 24". Includes our **Exclusive Engineering Features and the Best Warranty in the Industry!**



Trailer Colors

- Red
- Black
- Blue
- Safety Yellow



Part Number	Engine	Output*	Other Specifications
XF3TA2038CW	70HP (2 X 35HP) Vanguard by Toyota	20GPM @ 3,850 PSI	<ul style="list-style-type: none"> • Drive Triple V-Belt • Trailer Size 5' x 16' Deck • Tandem Axle, Powder Coated • Axle Rating 2 x 5,000 LB.
XF3TA1838CWCAL**	50HP (2 X 25HP) Vanguard by Toyota	18GPM @ 3,850 PSI	

*Output +/- 5% PSI and GPM vary as per elevation, engine RPM and nozzle size.

** CALIFORNIA AIR COMPLIANT

Exclusive Engineering Features

Dual Filter Intake System

We pre-plumb the pump intake so the draw water from the tank is dual filtered - one 80 mesh filter and the other a 50 mesh filter to protect the pump. This has proven to dramatically increase the pump life and reduce down time.

Pump

The pump systems we use are manufactured by General Pumps. The Emperor Series General Pump are proven with literally thousands in service worldwide. They are easy and inexpensive for service and we back them with a 10 year warranty. One advantage when operating both pump systems, you are running on 6 cylinders for extremely smooth operation.

Pump Saver System

We engineer all sewer jetter trailers with our "pump saver system" - that when the hose flow is released, the bypass water re-circulates back to the water tank. This keeps the head of the pump cool extending its life substantially.

TBDS™ (Total Belt Driven System)

All components are belt driven. The pump is Triple-V-Belt Driven. Belt driven reduces vibration and allows the pump to run at 1/2 RPM. This extends operational life, especially vs. gear driven power plants.

Chemical Application

The equipment operator can control the concentration levels at the machine and controls the chemical concentration depending on the job needs.

Quick Antifreeze System

Our sewer jetter trailer units come with our quick antifreeze system where you close one valve and open the antifreeze ball valve - then run the machine for 30 seconds and the entire system is antifreezed. Start the machine - then recapture the antifreeze in the antifreeze tank and re-attach the jetter nozzle and you are ready to jet!



Xtreme Flow III
Cold Water Jetter Series
Our most popular dual engine cold water jetter.
Used by professionals around the world.

Over 30 Years of Building Quality Equipment!



HotJetUSA[®]
DRAIN LINE JETTING EQUIPMENT

XtremeFlow[®] III
Cold Water Jetter Series



Shown With Upgrades



Shown With Upgrades



Shown With Upgrades

POWERFUL • BUILT TO LAST • BEST WARRANTY

This unit offers unbelievable versatility - you have the option to run 4 hose sizes... 1/2", 3/8", 1/4" and 1/8" so you can clean small lateral drains to storm drains when optioned with the 2nd rear hose reel and the "lateral drain" packages. Clean drain sizes from 2" to 24". Built for the service drain expert - this unit combines 2 of our power plates for a total of 70 HP and output of 20 GPM @ 3,850 PSI (+/-)! This unit is hot water upgradeable. Super price competitive and offers features and performance on matching units that cost 2 x's as much.

PUMP

- 2 - General Premium Emperor Series Pumps - TSF Series
- Triple Power V-Belt Driven
- Dual Safety Adjustable Blow Off Valves and Pump Saver System
- Dual Hose Pulsation Controls

MOTOR DESCRIPTION

- 2 - 35HP Vanguard (Manufactured by Toyota) Gas Engines
- Low Engine Oil/High Temperature Auto Shutdown System
- 14 Gallon Fuel Tanks
- Rear Throttle Control

HOSE & HOSE REELS

- Large Variable Speed Hose Reel with 500' of 1/2" Jetting Hose Rated @ 16,000 PSI Burst with 120° Thumb Control Guide Arm
- Mid-Sized Variable Hose Reel with 300' of 3/8" Jetting hose rated @ 12,000 PSI Burst with 120° Thumb Control Guide Arm
- Small Manual Hose Reel with 100' of 3/8" Steel Braided Hose for Power Washing or to run the lateral system

SAFETY FEATURES

- 10' Safety Colored Leader Hose
- 1/2" and 3/8" "Stinger" Pipes Included
- Rotary Safety / Beacon Light
- Gloves, Eye Protection and Full Safety Operating Manuals included
- Over PSI Safety Pop-off Valve

GENERAL SPECIFICATIONS

- 330 Gallon Water Capacity
- Molded HDP Water Tank(s)
- Low Water "Shut Off" Feature
- 2" x 36" Tiger Tail Hose Protector
- Adjustable Pressure Relief/Control Valve(s)
- Rear LED Lighting
- 2" Fast Fill

ACCESSORIES/UPGRADES AVAILABLE

- Portable Reel with 100' 1/4" Jetting Hose
- Solid State Remote Control
- 12 Volt Rear Power Connection for Spot Light or Camera
- HD Lockable Side Tool Boxes
- Customized Signage
- Warthog Nozzles
- Hot Water Available
- 660 Gallon Water Capacity with 14,000lb rated trailer

NOZZLES

- 1/2" - Lazer, Ram
- 3/8" - Lazer, Ram, Spinner and De-Greaser / De-Icer
- Power Wash Nozzles Included

TRAILER DESCRIPTION

- Full Premium Powder Coat
- Rugged, Specially Engineered Trailer to Haul the Equipment and Water Load
- Leaf Spring Axles Cushion and Distribute the Weight for Easy Towing
- 5'x16' Tandem Axle
- Tandem Axle (2 x 5,000 lb)
- Dual Axle Brake - DOT Legal in all 50 States

OVERALL DIMENSIONS

- Overall Length 18' 6" inc. hitch
- Deck Length 14'
- Height 7' with safety light
- Overall Deck Width 7'
- Weight 3,680 lbs.
- Weight (Full Load) 7,260 lbs.

DISTRIBUTED BY:

Manufactured by



14773 Heritage Crest Way • Riverton, UT 84065
1-800-624-8186

www.HotJetUSA.com

REF. 11242015