



Winterization Check List

- Window wash fluid added to anti-freeze tank.
- Anti-freeze valve open & main water feed valve closed.
- Main water feed tank drained (if applicable) add windshield wash fluid to keep from freezing. This will be done when anti-freezing the bypass line too.
- Soap Tank drained (if applicable) or add windshield wash fluid to keep from freezing if necessary.
- Main pump system anti-frozen.
- System blown out or window wash fluid run through system (from pump head to the hose reels).
- Bypass line anti-frozen (if applicable). This is done by running the unit with no valves open for 10-15 seconds in a bypass mode.
- Water tank fill hose or garden hose drained out or removed.
- Down-stream soap valve removed and stored (if applicable).
- Cover trailer jetter or store out of weather.

General service check list for storage longer than 30 days:

- Drain engine & pump oil.
- Treat fuel tanks or drain both gas & diesel.
- Check belts for wear.
- Check all Fasteners / nuts and bolts.
- Remove battery and get ready for storage with trickle charger.
- Check air pressure on all tires and spares.
- Check all hoses for excessive wear and replace if necessary.
- Check and clean all nozzles, this should be done after every job. A clean nozzle is a happy nozzle.

**If you have any questions or concerns please do not hesitate to call me
Chester Axley / Service Manager @ HotJet USA**

1-800-624-8186

www.HotJetUSA.com