

Over 30 Years of Building Quality Equipment!

CLEANS UP TO 12" LINES



SPECIALIZING IN MID-RANGE JETTERS

HotJet's Xtreme Flow Drain Line Jetters are engineered for the Rooter and Plumber Professional and built to tackle the toughest blockages. Easy to operate and priced right - the unit will handle small lateral lines with the jumper hose assembly as well as larger lines up 12". the unit includes our exclusive engineering features and the best warranty in the industry!



- Trailer Colors**
- Red
 - Black
 - Blue
 - Safety Yellow



Part Number	Engine	Output*	Other Specifications
XF2TA1038CW	35HP Vanguard by Toyota	10GPM @ 4,000 PSI	<ul style="list-style-type: none"> • Drive Triple V-Belt • Trailer Size 4' x 12' Deck • Tandem Axle, Powder Coated • Axle Rating 2 x 3,500 LB.
XF2TA9038CWCAL**	25HP Vanguard by Toyota	9GPM @ 3,850 PSI	
XF2TA1230CW	35HP Vanguard by Toyota	12GPM @ 3,000 PSI	

*Output +/- 5% PSI and GPM vary as per elevation, engine RPM and nozzle size.

** CALIFORNIA AIR COMPLIANT

Exclusive Engineering Features

Dual Filter Intake System

We pre-plumb the pump intake so the draw water from the tank is dual filtered - one 80 mesh filter and the other a 50 mesh filter to protect the pump. This has proven to dramatically increase the pump life and reduce down time.

Pump

The pump systems we use are manufactured by General Pumps. The Emperor Series General Pump are proven with literally thousands in service worldwide. They are easy and inexpensive for service and we back them with a 10 year warranty. One advantage when operating both pump systems, you are running on 6 cylinders for extremely smooth operation.

Pump Saver System

We engineer all sewer jetter trailers with our "pump saver system" - that when the hose flow is released, the bypass water re-circulates back to the water tank. This keeps the head of the pump cool extending its life substantially.

TBDS™ (Total Belt Driven System)

All components are belt driven. The pump is Triple-V-Belt Driven. Belt driven reduces vibration and allows the pump to run at 1/2 RPM. This extends operational life, especially vs. gear driven power plants.

Chemical Application

The equipment operator can control the concentration levels at the machine and controls the chemical concentration depending on the job needs.

Quick Antifreeze System

Our sewer jetter trailer units come with our quick antifreeze system where you close one valve and open the antifreeze ball valve - then run the machine for 30 seconds and the entire system is antifreezed. Start the machine - then recapture the antifreeze in the antifreeze tank and re-attach the jetter nozzle and you are ready to jet!



Xtreme Flow II Cold Water Jetter Series

Over 30 Years of Building Quality Equipment!



HotJetUSA®

SPECIALIZING IN MID-RANGE JETTERS

XtremeFlow® II

Cold Water Jetter Series



POWERFUL • BUILT TO LAST • BEST WARRANTY

This is most popular jetter trailer package for the professional Rooter/Plumber and smaller cities. This jetter trailer is a super combination of high PSI (3,850 or 3,000) with great output GPM (10 or 12) to clean nearly any blockage in lines up to 12". Super price competitive and looks better than units that cost 3x's the price! The super dependable Vanguard Power Plant (made by Toyota) combined with General's Premium Emperor Series Pump is a bullet proof engineering design. Add the jumper hose reel for laterals and this unit becomes two jettors in one! With a Warthog Nozzle this unit has plenty of power to cut roots and nearly any blockage.

GENERAL SPECIFICATIONS

- 330 Gallon Water Capacity
- Molded HDP Water Tank
- Low Water "Shut Off" Feature
- 2" x 36" Tiger Tail Hose Protector
- Adjustable Pressure Relief/Control Valve(s)
- Rear LED Lighting
- 2" Fast Fill

PUMP

- General Premium Emperor Series Pump - TSF Series
- Triple Power V-Belt Driven
- Dual Safety Adjustable Blow Off Valves and Pump Saver System
- Dual Hose Pulsation Controls

MOTOR DESCRIPTION

- 35HP Vanguard (Manufactured by Toyota) Gas Engine
- Low Engine Oil/High Temperature Auto Shutdown System
- 14 Gallon Fuel Tank
- Rear Throttle Control

DISTRIBUTED BY:

HOSE & HOSE REELS

- 300' of 3/8" Jetting hose rated @ 12,000 PSI Burst with 120° Thumb Control Guide Arm

NOZZLES

- 1/2" - Lazer, Ram
- 3/8" - Lazer, Ram, Spinner and De-Greaser / De-Icer
- Power Wash Nozzles Included

SAFETY FEATURES

- 10' Safety Colored Leader Hose
- 1/2" and 3/8" "Stinger" Pipes Included
- Rotary Safety / Beacon Light
- Gloves, Eye Protection and Full Safety Operating Manuals included
- Over PSI Safety Pop-off Valve

UPGRADES AVAILABLE

- 660 Gallon Water Capacity with 14,000 lb rated trailer

TRAILER DESCRIPTION

- Full Premium Enamel Paint
- Rugged, Specially Engineered Trailer to Haul the Equipment and Water Load
- Leaf Spring Axles Cushion and Distribute the Weight for Easy Towing
- 4'x12' Tandem Axle
- Tandem Axle (2 x 3,500 lb)
- Dual Axle Brake - DOT Legal in all 50 States

OVERALL DIMENSIONS

- Overall Length 16' 6" incl. hitch
- Deck Length 12'
- Height 8' w/safety light
- Overall Deck Width 7'
- Weight Dry 2,560 lbs
- Weight Full Load 4,980 lbs

Manufactured by



14773 Heritage Crest Way • Riverton, UT 84065

1-800-624-8186

www.HotJetUSA.com